

Compositional Ordering and Stability in Nanostructured, Bulk Thermoelectric Alloys



D.L. Medlin¹, P.A. Sharma¹, J.D. Sugar¹, J. Lensch-Falk¹, M. Hekmaty¹,
S. Faleev^{1,3}, F. Léonard¹, S. Whalen²


¹Materials Physics Department, 8756, Sandia National Laboratories, Livermore, CA

²Power Systems Component Development Dept., 2547 Sandia National Laboratories, Albuquerque, NM

³Present address: Seagate Technology, Pittsburgh PA

Problem

Materials Science Challenge for Thermoelectrics



A conflict of size-scales

- Improve conversion efficiency

thermoelectric materials figure-of-merit

$$ZT = \frac{S^2 \sigma}{K} T$$

Seebeck Coefficient S , Electrical Conductivity σ , Thermal Conductivity K

→ Nanostructuring

- Generate useful amounts of power or cooling capacity


→ Require materials on the mm to cm size-scale.

Nanostructured Bulk Thermoelectrics

- Emerging routes to improve bulk TE performance by embedding high densities of interfaces.
 - phonon scattering to reduce κ
 - energy filtering, quantum confinement to improve $S^2\sigma$
- Need for better understanding of formation mechanisms & stability of embedded nanostructures and quantitative link between structure and properties.

Goals of our study:


- Establish the atomic mechanisms that govern formation and stability of embedded interfaces in nanostructured bulk thermoelectrics.
- Understand links between embedded nanostructure and thermoelectric performance..



Approach

Our approach: Connect nanostructure to properties through detailed microscopy and theory

Synthesize nanostructured, bulk thermoelectric alloys




Measure transport properties




Seebeck coefficient
Thermal conductivity
Electrical resistivity
Carrier concentrations

Measure nanostructure using advanced microscopies




Develop theory to connect transport to nanostructure




Results

We are investigating mechanisms of nanostructure formation in rock-salt tellurides

Example: Ag₂Te Nano-inclusions in AgSbTe₂



Monoclinic Ag₂Te Adopts multiple variants in rock-salt matrix




J.D. Sugar, D.L. Medlin, J. Alloys and Compounds 2009

- High thermoelectric energy conversion efficiency in complex, rock-salt structured tellurides has been attributed to long-range compositional superlattice ordering.
- However, our investigation has shown that apparent "superlattice" reflections in diffraction from such tellurides can actually arise from topotactically aligned nanoprecipitates.

Results



We are linking thermoelectric performance to evolution of internal interfacial structure

Sb₂Te₃ growth reduces Seebeck coefficient



P. Sharma, J.D. Sugar, D.L. Medlin (2009), in preparation.


Sb₂Te₃ plates form during Annealing Of Sb-rich AgSbTe₂ (Ag_{16.7}Sb₃₀Te_{53.3})



- Formation of interconnected network degrades properties.
- Heterogeneous nucleation (e.g., at grain boundaries) must be suppressed.

We are investigating atomic mechanisms governing nanoprecipitate growth and stability

Example: Atomic Step at AgSbTe₂/Sb₂Te₃ interface



Resolve Burgers vector (b) of step into components normal and parallel to interface

$$b_n = (a_{\text{step}} - c_{\text{step}}) / (3\sqrt{3}) [111]$$


• mismatch of step heights.

$$|b_n| = 0.3747 \text{ Å}$$

$$b_t = \frac{a_{\text{step}}}{6} [\bar{1}2\bar{1}]$$

• Analogous to Shockley Partial Dislocation


$$|b_t| = 2.48 \text{ Å}$$



- Generic mechanism for transformation from rock-salt to tetradymite tellurides.
- Insight concerning misfit accommodation and morphological stability.


We have developed a theory of TE enhancement due to nano-inclusions

Charge Transfer at metal/semiconductor interface produces energy dependent scattering.



S. Faleev & F. Léonard, Physical Review B, 2008

Predicted enhancement of ZT with metallic nano-inclusions



- Enhancement of Seebeck coefficient by filtering low energy charge carriers ($\tau \sim E^{-3/2}$).
- Suppression of both electronic and phononic contributions to thermal conductivity.
- Our current experiments on Ag₂Te nano-inclusions in PbTe will seek to test this theory

Significance

Impact

- Work is providing fundamental understanding of mechanisms underpinning interface formation and stability in nanostructured bulk thermoelectric materials.
- New insights from theory and experiment are establishing links between nanostructure and thermoelectric properties.
- Results from this project provide foundational knowledge for new microstructural strategies to tailor advanced thermoelectric materials.

Publications:

- S.V. Faleev and F. Léonard, "Theory of Enhancement of Thermoelectric Properties of Materials with Nano-inclusions", Physical Review B 77 (2008) 214304.
- J.D. Sugar, D.L. Medlin, "Precipitation of Ag₂Te in the Thermoelectric Material AgSbTe₂" Journal of Alloys and Compounds 478 (2009) 75-82
- D.L. Medlin and G.J. Snyder, "Interfaces in Bulk Thermoelectric Materials" Current Opinion in Colloid and Interface Science 14 (2009) 226-235 (Invited Review Article).
- P. A. Sharma, J.D. Sugar, D.L. Medlin "Link between Thermoelectric Figure of Merit and Microstructure in Nanostructured AgSbTe₂" In preparation for submission to Physical Review B (2009).
- D.L. Medlin and J.D. Sugar, "Interfacial Defect Structure at Sb₂Te₃ Plates in the Thermoelectric Compound AgSbTe₂" in preparation for submission to Scripta Materialia (2009).